


DO NOT SCALE DRAWING

THE INFORMATION CONTAINED HEREIN IS THE EXCLUSIVE PROPERTY OF VPC AND IS PERMITTED FOR USE BY THE CUSTOMER ONLY. THE DATA SHALL NOT BE DUPLICATED, USED, OR DISCLOSED IN WHOLE OR IN PART FOR ANY PURPOSE OTHER THAN TO MAINTAIN THE EQUIPMENT PROVIDED.

REV	DESCRIPTION	DATE	ENGINEER
E	ECN #12774	10/6/22	J HARDIGREE

- 5 [] REPRESENTS CURRENT REVISION LEVEL
- 4 APPROXIMATE LOCATIONS FOR PIECE PART MOLD CAVITY IDENTIFIER
- 3 MAX CABLE BUNDLE EFFECTIVE DIAMETER = 0.77 IN
CLAMP CAN BE INVERTED FOR SMALLER CABLE BUNDLES
2. MATERIALS:
OUTER SHELL COMPONENTS & HANDLE - REINFORCED THERMOPLASTIC
DECALS - VINYL OVER POLYESTER
DRIVE SYSTEM - HEAT TREATED BeCu AND BRASS, Ni PLATED
HARDWARE - STAINLESS STEEL
1. FOR MORE INFORMATION, VISIT VPC.COM.
- NOTES:

CUSTOMER DRAWING


VPC VIRGINIA PANEL CORPORATION

ITA, i2 MICRO ICON,
120/12 POS HYBRID

RELATIVE CONNECTOR POSITIONS AND WIRE ROUTING ARE GENERIC AND MAY VARY WITH PINOUT	DWG.NO.	REV
DIMENSIONS ARE SHOWN AS: [MILLIMETERS] INCHES	410130104	E
SCALE NONE	CAGE CODE 18117	SHEET 1 OF 1