


DRAWING NOT TO SCALE  
FOR REFERENCE ONLY

THE INFORMATION CONTAINED HEREIN IS THE EXCLUSIVE PROPERTY OF VIRGINIA PANEL CORPORATION AND IS SUBMITTED FOR USE BY THE CUSTOMER ONLY. THE DATA SHALL NOT BE DUPLICATED, USED OR DISCLOSED IN WHOLE OR IN PART FOR ANY PURPOSE OTHER THAN TO MAINTAIN THE EQUIPMENT PROVIDED. CONSULT WITH VIRGINIA PANEL CORPORATION ENGINEERING IF MORE DETAIL IS REQUIRED.



6. Insertion Loss = -2.762 db max  
5. Maximum Operating Frequency = 3 GHz
- 4 MCX PLUG  
3 RG316 TAN M17/113 (50 OHM, 3 GHZ)  
2 MICRO COAX, ITA, 3 GHZ

NOTES:

DIMENSIONS ARE SHOWN AS  
[MILLIMETERS]  
INCHES

CUSTOMER DRAWING		
VPC Patchcord Designer		
WWW.VPC.COM		
Coax Patchcord, ITA, Micro Coax, 36", RG316 Tan, to MCX Plug, (3 GHz)		
SIZE A	CAGE CODE 18117	PART# 7-361116582-036
SCALE: NONE	DATE: 05/01/2025	SHEET 1 OF 1