


DRAWING NOT TO SCALE
FOR REFERENCE ONLY

THE INFORMATION CONTAINED HEREIN IS THE EXCLUSIVE PROPERTY OF VIRGINIA PANEL CORPORATION AND IS SUBMITTED FOR USE BY THE CUSTOMER ONLY. THE DATA SHALL NOT BE DUPLICATED, USED OR DISCLOSED IN WHOLE OR IN PART FOR ANY PURPOSE OTHER THAN TO MAINTAIN THE EQUIPMENT PROVIDED. CONSULT WITH VIRGINIA PANEL CORPORATION ENGINEERING IF MORE DETAIL IS REQUIRED.



6. Insertion Loss = -1.364 db max
5. Maximum Operating Frequency = 3 GHz
4. SMB PLUG
3. RG316 TAN M17/113 (50 OHM, 3 GHZ)
2. MICRO COAX, RECEIVER, 3 GHZ

NOTES:

DIMENSIONS ARE SHOWN AS
[MILLIMETERS]
INCHES

CUSTOMER DRAWING		
VPC Patchcord Designer		
WWW.VPC.COM		
Coax Patchcord, Receiver, Micro Coax, 8", RG316 Tan, to SMB Plug, (3 GHz)		
SIZE	CAGE CODE	PART# 7-362 116 527-008
A	18117	
SCALE: NONE	DATE: 04/28/2024	SHEET 1 OF 1