

			KEYING PL	UGL	OCATIONS	5			
PATTERN 1					PATTERN 4				
RECIEVER		П	ПА		RECIEVER			ПА	
PIN A INSTALLED	PIN C INSTALLED	SCREW A OPEN	SCREW C OPEN		PIN A OPEN	PIN C INSTALLED		SCREW A	SCREW C OPEN
PIN B OPEN	PIN C OPEN	SCREW B	SCREW D		PIN B OPEN	PIN D INSTALLED		SCREW B	SCREW D OPEN
PATTERN 2					PATTERN 5				
RECIEVER		П	ПА		RECIEVER			ПА	
PIN A	PINC	SCREW A	SCREW C		PIN A	PIN C		SCREW A	SCREW C
INSTALLED	OPEN	OPEN	INSTALLED		OPEN	INSTALLED		INSTALLED	OPEN
PIN B	PIN D	SCREW B	SCREW D		PIN B	PIN D		SCREW B	SCREW D
INSTALLED	OPEN	OPEN	INSTALLED		INSTALLED	OPEN		OPEN	INSTALLE
					-				
PATTERN 3					PATTERN 6				
RECIEV ER		П	ПА		RECIEVER			ПА	
PIN A	PINC	SCREW A	SCREW C		PIN A	PIN C		SCREW A	SCREW C
INSTALLED	OPEN	OPEN	INSTALLED		OPEN	OPEN		INSTALLED	INSTALLE
PIN B	PIN D	SCREW B	SCREW D		PIN B	PIN D		SCREW B	SCREW D
OPEN	INSTALLED	INSTALLED	OPEN		INSTALLED	INSTALLED		OPEN	OPEN

SOLIDWORKS DRAWING FILE	CUSTOME					
	DIMENSIONS ARE SHOWN AS:					
	(millimeters) INCHES .XXX CRITICAL CHARACTERISTIC					
	REMOVE BURRS. BREAK SHARP EDGES.					
IDWORH	MATERIAL					
SOL	FINISH					
	3					

MATING ITA	PROTECTIVE COVER	VERTICAL HINGED MOUNTING FRAME	
410104273 410104118	310113158	310113341	
	5	4	