



3

TABLE 1		
PART NUMBER	DESCRIPTION	RECEIVER CUTOUT SPACING
410130101	ITA, i2 Micro iCon, 168 Position	1.00 [25.40]
410130104	ITA, i2 Micro iCon, 120/12 Position Hybrid	1.00 [25.40]
410130106	ITA, i2 Micro iCon, 168 Position with Oversized Backshell	2.19[55.63]
410130115	ITA, i2 Micro iCon, 120/12 Position Hybrid with Oversized Backshell	2.19[55.63]

*SPACING IS APPLICATION SPECIFIC, .80" MINIMUM, 1.00" RECOMMENDED

3 SEE TABLE 1 FOR MINIMUM DISTANCE OF SUBSEQUENT SIDE BY SIDE CUTOUTS.

DO NOT SCALE DRAWING

3

THE INFORMATION CONTAINED HEREIN IS THE EXCLUSIVE PROPERTY OF VPC AND IS PERMITTED FOR USE BY THE CUSTOMER ONLY. THE DATA SHALL NOT BE DUPLICATED, USED, OR DISCLOSED IN WHOLE OR IN PART FOR ANY PURPOSE OTHER THAN TO MAINTAIN THE EQUIPMENT PROVIDED.

2

2

SIZE CAGE CODE DWG.NO. 310130105 SCALE: NONE 310130105 7/26/11 SHEET 2 OF 2

7

REV

G

1

D