

- VTAC INSERTS:
- VTAC CONTACT = ALLOY 7025 OUTER SHELL = BLUE/BLACK LCP
- USB 3.0 TYPE A FEMALE:
- HOUSING = THERMOPLASTIC
- CONTACT = COPPER ALLOY
- SHELL = STAINLESS STEEL

1. FOR APPLICATION USE AND CARE INFORMATION CONSULT VPC USERS GUIDE @ WWW.VPC.COM NOTES:

4

З

J2

J2

J2

J2

J2

13

14

15

16

3

1

4

5

8

Ρ1

Ρ1

2

5

7

1	I			
DESCRIPTION		DATE	ENGINEER	
ECN #11245	3/	1/2021	C CHURCH	
				D
VTAC."SS				С
	·			
				В
	CUSTO	MER D	RAWING	А
	<b>PC</b> Virginia Panel Corporation			
		C≣ Virginia CB ADA		
RELATIVE CONNECTOR POSITIONS AND WIRE ROUTING ARE GENERIC AND MAY VARY WITH PINOUT	VTAC R	CV TO U	SB 3.0 FML	
DIMENSIONS ARE SHOWN AS:		5101701		
[MILLIMETERS] INCHES	scale 3:2	CAGE CODE 18117	SHEET 1 OF 1	
	1			