

SIGNAL

Receiver

ITA

QuadraPaddle, 5 Amp, 22-28 AWG



610 138 216

610 138 109

TriPaddle, 7 Amp, 20-24 AWG



610 110 101



610 110 108

COAX

Receiver

ITA

Micro Coax, 50 Ohm, 3 GHz



610 140 101

610 141 101

75 Ohm Coax, 3 GHz



610 104 157

610 103 169

20/26 GHz Coax, 50 Ohm (only available as a patchcord)



610 102 119

610 102 118

50 GHz Micro Coax (only available as a patchcord)



610 140 108

610 141 108

POWER

Receiver

ITA

Micro Power, 21 Amp, 12-14 AWG



610 142 101

610 143 101

High Power, 150 Amp, 2 AWG



610 149 101

610 150 101

FIBER OPTIC

Receiver

ITA

Multimode Glass Fiber, 62.5/125 and 50/125 (only available as a patchcord)



610 113 172

610 113 173

Polymer Optic Fiber, 980 (only available as a patchcord)



610 113 170

610 113 171

HIGH SPEED DIGITAL

VTAC

12.5+ Gbps

*Inserts are reversible-
can be used as a Receiver or ITA Insert




610 151 103

VTAC

Right Angle
Insert

10+ Gbps



610 151 104

VTAC

Vertical
Header

12.5+ Gbps



610 151 107

*See back for a full list of VPC's high performance contacts.



QUADRAPADDLE RECEIVER CONTACTS

610 138 117	Signal Contact, Receiver, QuadraPaddle, 5 Amp, Male Adapter, .025" Round Post
610 138 118	Signal Contact, Receiver, QuadraPaddle, 5 Amp, Male Adapter, .025" Square Post for Wire Wrap
610 138 200	Signal Contact, Receiver, QuadraPaddle, 5 Amp, Twin Female
610 138 216*	Signal Contact, Receiver, QuadraPaddle, 5 Amp, 22-28 AWG

QUADRAPADDLE ITA CONTACTS

610 138 109*	Signal Contact, ITA, QuadraPaddle, 5 Amp, 22-24 AWG
610 138 112	Signal Contact, ITA, QuadraPaddle, 5 Amp, 26-30 AWG
610 138 115	Signal Contact, ITA, QuadraPaddle, 5 Amp, .025" Round Post
610 138 122	Signal Contact, ITA, QuadraPaddle, 5 Amp, .025" Square Post for Wire Wrap with Anti-Rotation

TRIPADDLE RECEIVER CONTACTS

610 110 101*	Signal Contact, Receiver, TriPaddle, 7 Amp, 20-24 AWG
610 110 128	Signal Contact, Receiver, TriPaddle, 10 Amp, 14-18 AWG
610 110 167	Signal Contact, Receiver, TriPaddle, 7 Amp, 26-28 AWG
610 110 177	Signal Contact, Receiver, TriPaddle, 10 Amp, 14-18 AWG
610 110 179	Signal Contact, Receiver, TriPaddle, 5 Amp, .025" Round Post

TRIPADDLE ITA CONTACTS

610 110 108*	Signal Contact, ITA, TriPaddle, 7 Amp, 20-24 AWG
610 110 113	Signal Contact, ITA, TriPaddle, 7 Amp, .025" Square Post for Wire Wrap
610 110 129	Signal Contact, ITA, TriPaddle, 10 Amp, 14-18 AWG
610 110 169	Signal Contact, ITA, TriPaddle, 7 Amp, 26-28 AWG

MINI POWER RECEIVER CONTACT

610 116 112	Mini Power Contact, Receiver, 65 Amp, 8 AWG
-------------	---

MINI POWER ITA CONTACTS

610 115 124	Mini Power Contact, ITA, 65 Amp, 8 AWG
610 115 125	Mini Power Contact, ITA, 65 Amp, 8 AWG

MICRO POWER RECEIVER CONTACTS

610 142 101*	Micro Power Contact, Receiver, 21 Amp, 12-14 AWG
610 142 102	Micro Power Contact, Receiver, 21 Amp, PCB Mount

MICRO POWER ITA CONTACTS

610 143 101*	Micro Power Contact, ITA, 21 Amp, 12-14 AWG
--------------	---

HIGH POWER RECEIVER CONTACT

610 149 101*	High Power Contact, Receiver, 150 Amp, 2 AWG
--------------	--

HIGH POWER ITA CONTACT

610 150 101*	High Power Contact, ITA, 150 Amp, 2 AWG
--------------	---

THERMOCOUPLE RECEIVER CONTACTS

610 113 131	Thermocouple Contact, Receiver, Chromel, Type K (°C)
610 113 132	Thermocouple Contact, Receiver, Alumel, Type K (°C)
610 113 148	Thermocouple Contact, Receiver, Constantan, Type T (°C)
610 113 168	Thermocouple Contact, Receiver, Copper, Type T (°C)

THERMOCOUPLE ITA CONTACTS

610 113 133	Thermocouple Contact, ITA, Chromel, Type K (°C)
610 113 134	Thermocouple Contact, ITA, Alumel, Type K (°C)
610 113 149	Thermocouple Contact, ITA, Constantan, Type T (°C)
610 113 169	Thermocouple Contact, ITA, Copper, Type T (°C)

PNEUMATIC RECEIVER CONTACTS

610 131 101	Pneumatic Contact, Receiver, Ferruleless Fitting, for 3/8" OD, 1/4" [9.5 x 6 mm] ID Tubing
610 131 104	Pneumatic Contact, Receiver, Hose Barb, for 3/8" [9.5 mm] ID Tubing
610 131 107	Pneumatic Contact, Receiver (with valve), Hose Barb, for 1/8" [3.2 mm] ID Tubing
610 131 111	Mini Pneumatic Contact, Receiver, Push-in Fitting, for 4 mm OD Tubing
610 131 112	Mini Pneumatic Contact, Receiver, Push-in Fitting, for 6 mm OD Tubing
610 132 105	Pneumatic Contact, Receiver, Hose Barb, for 1/8" [3.2 mm] ID Tubing

PNEUMATIC ITA CONTACTS

610 132 101	Pneumatic Contact, ITA, Ferruleless Fitting, for 3/8" OD, 1/4" [9.5 x 6 mm] ID Tubing
610 132 104	Pneumatic Contact, ITA, Hose Barb, for 3/8" [9.5 mm] ID Tubing
610 131 106	Pneumatic Contact, ITA, Hose Barb, for 1/8" [3.2 mm] ID Tubing
610 132 111	Mini Pneumatic Contact, ITA, Push-in Fitting, for 4 mm OD Tubing
610 132 112	Mini Pneumatic Contact, ITA, Push-in Fitting, for 6 mm OD Tubing

MINI COAX RECEIVER CONTACTS

610 104 114	Mini Coax Contact, Receiver, 1 GHz, RG316
610 104 140	Mini Coax Contact, Receiver, 1 GHz, with two .025" Square Posts for Wire Wrap
610 104 141	Mini Coax Contact, Receiver, 1 GHz, RG178
610 104 160	Mini Coax Contact, Receiver, 1 GHz, Right Angle Posts for PCB Mount

MINI COAX ITA CONTACTS

610 103 115	Mini Coax Contact, ITA, 1 GHz, RG316
610 103 129	Mini Coax Contact, ITA, 1 GHz, with two .025" Square Posts for Wire Wrap
610 103 130	Mini Coax Contact, ITA, 1 GHz, RG178
610 103 136	Mini Coax Contact, ITA, 1 GHz, 24 AWG
610 103 161	Mini Coax Contact, ITA, 1 GHz, 24 & 26 AWG Twisted Pair
610 103 172	Mini Coax Contact, ITA, 1 GHz, 22 AWG
610 103 184	Mini Coax Contact, ITA, 1 GHz, 22 AWG Twisted Pair

MICRO COAX RECEIVER CONTACTS

610 140 101*	Micro Coax Contact, Receiver, 3 GHz, RG316
610 140 102	Micro Coax Contact, Receiver, 3 GHz, RG178
610 140 103	Micro Coax Contact, Receiver, 2 GHz, RG179
610 140 104	Micro Coax Contact, Receiver, 10.5 GHz, RG316 Double Shield
610 140 108*	Micro Coax Contact, Receiver, 50 GHz

MICRO COAX ITA CONTACTS

610 141 101*	Micro Coax Contact, ITA, 3 GHz, RG316
610 141 102	Micro Coax Contact, ITA, 3 GHz, RG178
610 141 103	Micro Coax Contact, ITA, 2 GHz, RG179
610 141 104	Micro Coax Contact, ITA, 10.5 GHz, RG316 Double Shield
610 141 108*	Micro Coax Contact, ITA, 50 GHz

75 OHM COAX RECEIVER CONTACT

610 104 157*	Coax Contact, Receiver, 75 Ohm, RG179
--------------	---------------------------------------

75 OHM COAX ITA CONTACT

610 103 169*	Coax Contact, ITA, 75 Ohm, RG179
--------------	----------------------------------

75 OHM HD COAX RECEIVER CONTACT

610 102 133	Coax Contact, Receiver, 75 Ohm HD, sm59/U Belden 1855A, 3GHz
-------------	--

75 OHM HD COAX ITA CONTACT

610 102 132	Coax Contact, ITA, 75 Ohm HD, sm59/U Belden 1855A, 3GHz
-------------	---

20/26 GHZ COAX RECEIVER CONTACTS

610 102 109	Coax Contact, Receiver, 20/26 GHz, SF142B
610 102 116	Coax Contact, Receiver, 20 GHz, RG 223, Crimp, (12 GHz using RG 223)
610 102 119*	Coax Contact, Receiver, 20/26 GHz, Flex 402
610 102 135	Coax Contact, Receiver, 20/26 GHz with SMA Adapter

20/26 GHZ COAX ITA CONTACTS

610 102 110	Coax Contact, ITA, 20/26 GHz, SF142B
610 102 117	Coax Contact, ITA, 20 GHz, RG 223, Crimp (12 GHz using RG 223)
610 102 118*	Coax Contact, ITA, 20/26 GHz, Flex 402
610 102 134	Coax Contact, ITA, 20/26 GHz with SMA Adapter

40 GHZ COAX RECEIVER/ITA CONTACT

610 102 114	Coax Contact, Receiver and ITA, 40 GHz
-------------	--

VTAC

610 151 103*	VTAC, High Speed Insert, Receiver/ITA, SIM, 12.5 Gbps
VTAC RIGHT ANGLE	
610 151 104*	VTAC, High Speed Insert, Receiver/ITA, SIM, Right Angle
VTAC VERTICAL HEADER	
610 151 107*	VTAC, High Speed Insert, Receiver/ITA, SIM, Vertical Header

FIBER OPTIC RECEIVER CONTACTS

610 113 170*	Mini Fiber Optic Contact, Receiver, Polymer Optic Fiber
610 113 172*	Mini Fiber Optic Contact, Receiver, 62.5/125, Multimode

FIBER OPTIC ITA CONTACTS

610 113 171*	Mini Fiber Optic Contact, ITA, Polymer Optic Fiber
610 113 173*	Mini Fiber Optic Contact, ITA, 62.5/125, Multimode

*See front for an example of this contact. For more detailed information on all of VPC's contacts, visit vpc.com.